

FALUSÅPA

SWEDISH LINSEED OIL SOAP

FROM FALU RÖDFÄRG



FALUSÅPA

For centuries, we have produced our paint, with linseed oil as a natural ingredient. We can now also offer FALUSÅPA, the result of a more sustainable production process in which a greater proportion of the linseed is put to good use. FALUSÅPA is a traditional linseed oil soap made from Swedish linseed oil. It effectively removes dirt in both cold and warm water and is gentle on surfaces as well as to the environment. A natural product that is biodegradable.

FOR CLEANING OF WOODEN DECKING – AND MUCH MORE

Cleaning of wooden decking and patios is an ideal application for FALUSÅPA, but this versatile cleaning soap can be used on a wide variety of surfaces and for many different purposes. You can use it for everything from floor treatment and scrubbing wooden floors, brush cleaning, and stain removal to cleaning tiles, ceramic floors, kitchen worktops, and most other surfaces around the home. In addition to FALUSÅPA in canisters, there is also FALUSÅPA Spray, a lightly fragranced all-purpose cleaner supplied in a practical spray bottle. Its ready-to-use formula makes it easy to quickly clean surfaces in everyday use, while also being ideal for more thorough cleaning tasks.

HOW TO USE

Dilution: For lightly soiled surfaces, mix 50–100 ml of FALUSÅPA with 10 litres of water. For heavily soiled surfaces, mix 500–1,000 ml of FALUSÅPA with 10 litres of water. Apply the solution and allow it to work for 5-10 minutes before scrubbing with a brush. Then rinse thoroughly with water. When cleaning decking, patios, or wooden floors, always scrub in the direction of the wood grain.

Brush Cleaning: Coat the brush thoroughly with FALUSÅPA and work it into the bristles. Rinse thoroughly with water. If the paint in the bristles has started to dry, leave the brush standing in FALUSÅPA overnight.

Using FALUSÅPA Spray: Spray onto the dirty surface and leave for a minute or two. Wipe clean with a damp cloth. For an extra-fine finish, polish with a dry cloth afterwards.

TECHNICAL INFORMATION

FALUSÅPA

Contents: 15-30 % saponified linseed oil

pH-value: approximately 11

FALUSÅPA SPRAY

Contents: <5% saponified linseed oil, <0.01% fragrance

pH-value: approximately 10

Available in 1-litre and 5-litre containers, as well as a ready-to-use soap spray.

GOOD TO KNOW

- Linseed oil soap dissolves linseed oil paint and can attack aluminium surfaces.
- Avoid scrubbing brushes with stiff bristles, as they may damage the wood.
- Do not allow the soap solution to dry on the floor, as this may cause staining.
- Soap-scrubbed floors gradually lighten with repeated cleaning. Oak, in particular, lightens significantly because the oxalic acid naturally present in the wood reacts with the soap. This reaction can produce a dark brown to black surface, which is subsequently washed away with water.
- The final result of both treatment and cleaning may vary depending on the type of wooden flooring and the sanding finish.

Discover more tips, advice and practical uses at falurodfarg.com



Stora Kopparbergs Bergslags AB, Falu Rödfärg, 791 80 Falun.
Phone +46 23-78 23 25, info@falurodfarg.com, www.falurodfarg.com.